

statheros[®]
Precisely Engineered

World of Fixings



SGT C38 Concrete Gas Tool





Removable Magazine System

Keyless Jam Clearing

Multi-function Barrel System

Removable Magazine System

KEYLESS JAM CLEARING

Unplug magazine and unscrew barrel without getting extra tool to resume your work.

MULTI-FUNCTION BARREL SYSTEM (PATENTED)

Easiest barrel systems for different applications, magnetic or plastic, or whatever you see interesting.

REMOVABLE MAGAZINE SYSTEM

Easy to increase capacity to 40pins magazine for rapid shooters; or single shot user with pre-assembled clips / washers by taking of the magazine in a second.

MAGAZINE SYSTEM FOR WIDE VARIETY OF NAILS

C38HD and C65 can shoot 2.6mm shank nails without using different collation strips; SP series can shoot collation PAT nails.

ADDITIONAL FEATURES

New & modern design, optimized ergonomics, easy handling, very low backstroke, high efficiency system, light weight.

SHORT TRACK AND LONG TRACK OPTIONS AVAILABLE





SGT-C38

Dimensions (LxWxH)	400 x 360 x 100
Weight	3.78kg
Automatic piston return	Yes
Max. fastener driving rate	1200 / h
Fastener specifications	6.3mm Head Diameter 2.6mm x 15-40mm Regular Nails 3.0mm x 15-40mm Premium Nails
Fuel cell	SGC-165S
Sound power level	104 ± 2dB (A)
Base materials	Concrete Steel Block Masonry Brick (sand-lime) Wood
Applications	Tracking Electrician Wiring
Magazine capacity	30 (Short Track) / 40 (Long Track)
Power	90 J
Depth Adjustment	Yes
Operating Temperature Range	-10°C to 45°C
Approval	CE





GAS FOR NAIL GUNS

Product Code	Description	Fuel Cell Capacity (ml)	Weight of Fuel Cell (g)	For use with	Box Packing	Bulk Packing
SGC-165S	Gas for Gas Tools / 165mm	80	40	SGT C38	20	120 /200



MAGAZINE NAILS FOR GAS NAILER (FIXING IN CONCRETE AND STEEL)

Product Code	Base Material	Nail Diameter (mm)	Nail Length (mm)	For use with	Box Packing	Bulk Packing
--------------	---------------	--------------------	------------------	--------------	-------------	--------------

STANDARD

SGT 20	Concrete / Steel / Brick	2,6	20	SGT C38	1,000	5,000
SGT 25	Concrete / Steel / Brick	2.6	25	SGT C38	1,000	5,000
SGT 30	Concrete / Steel / Brick	2.6	30	SGT C38	1,000	5,000
SGT 35	Concrete / Steel / Brick	2.6	35	SGT C38	1,000	5,000
SGT 40	Concrete / Steel / Brick	2.6	40	SGT C38	1,000	5,000

PREMIUM

SGT15PXH	Steel	3,0 / 2,6	15	SGT C38	1,000	5,000
SGT17PXH	Concrete / Steel / Brick	3,0 / 2,6	17	SGT C38	1,000	5,000
SGT19PXH	Concrete / Steel / Brick	3,0 / 2,6	19	SGT C38	1,000	5,000
SGT22PXH	Concrete / Steel / Brick	3,0 / 2,6	22	SGT C38	1,000	5,000
SGT27PXH	Concrete / Steel / Brick	3,0 / 2,6	27	SGT C38	1,000	5,000
SGT32PXH	Concrete / Steel / Brick	3,0 / 2,6	32	SGT C38	1,000	5,000
SGT40PXH	Concrete / Steel / Brick	3,0 / 2,6	40	SGT C38	1,000	5,000

LOADING TABLE

Gas Nailer	Min Embedment Depth (mm)	Min Edge Distance (mm)	Allowable Capacity ¹			
			Concrete Compressive Strength			
			27 MPa (4000 psi)		40 MPa (6000 psi)	
			Tension (kN)	Shear (kN)	Tension (kN)	Shear (kN)
SGT22PXH	20	76	0.32	0.33	0.49	0.59

¹ Values are based on the lowest ultimate load with a safety factor of 5.0 applied.
* Information above is for reference only. On-site testing is highly recommended.

RFM CONSTRUCTION PRODUCTS (M) SDN BHD (Co. No. 926228-U)

No. 37, Jalan Serendah 26/41, Sekitar 26 Seksyen 26, 40400 Shah Alam, Selangor Darul Ehsan, Malaysia.

Tel (603) 5614 3186 | Fax (603) 5614 3187 | Email info@rfmcp.com | Website www.statheros.com

